

DIGITAL INSIDE GROOVE CALIPERS





1120-150A
type A

- Measure groove diameter
- Resolution: 0.01mm/0.0005"
- Buttons: on/off, set, mm/inch, preset (+, -) (type A), on/off, zero, mm/inch (type B), on/off, zero, mm/inch, ABS/REL, hold (type C)
- Battery CR2032
- Made of stainless steel
- Optional accessory: depth stop (code **6143**, for calipers with a width of 16mm), data output cable (code **7315-**, **7302-**, **7305-**, for type A or B calipers without built-in wireless)



1120-150B
type B

depth stop **6143**
(optional)



1120-150P
type C

No dust/waterproof (data output, automatic power off, preset, no need to add the width of the jaws on the reading)

(mm)

Code	Range	Type	Accuracy	L	a	b	c	d	e	Wireless
1120-150A	22-150mm/0.87-6"	A	±0.04mm	250	5	11	16	30	1	no
1120-150AWL										built-in wireless
1120-1501	35-150mm/1.38-6"	A	±0.06mm	250	6	17.5	16	60	1.5	no
1120-1501WL										built-in wireless
1120-200A	25-200mm/0.98-8"	A	±0.04mm	310	5	12.5	16	40	1	no
1120-200AWL										built-in wireless
1120-2001	40-200mm/1.57-8"	A	±0.06mm	310	7	20	16	70	2.5	no
1120-2001WL										built-in wireless
1120-300A	30-300mm/1.18-12"	A	±0.05mm	410	5	15	16	50	1.5	no
1120-300AWL										built-in wireless
1120-3001	50-300mm/1.97-12"	A	±0.07mm	410	8	25	16	80	2.5	no
1120-3001WL										built-in wireless
1120-500	40-500mm/1.57-20"	A	±0.07mm	680	5	20	24	90	2.2	no
1120-500WL										built-in wireless
1120-5001	60-500mm/2.36-20"	A	±0.08mm	680	10	30	24	120	3.4	no
1120-5001WL										built-in wireless
1120-5002	80-500mm/3.15-20"	A	±0.08mm	680	16	40	24	150	5.2	no
1120-5002WL										built-in wireless

No dust/waterproof (data output, automatic power off, no preset, need to add the width of the jaws on the reading)

(mm)

Code	Range	Type	Accuracy	L	a	b	c	d	e	Wireless
1120-150B	50-150mm/1.97-6"	B	±0.06mm	270	8	25	20	90	3.4	no
1120-200B	60-200mm/2.36-8"	B	±0.06mm	320	10	30	20	100	3.4	no
1120-300B	60-300mm/2.36-12"	B	±0.07mm	420	10	30	20	110	3.4	no

IP67 dust/waterproof (no data output, no automatic power off, set zero after power on each time, no preset, need to add the width of the jaws on the reading)

(mm)

Code	Range	Type	Accuracy	L	a	b	c	d	e
1120-150P	22-150mm/0.87-6"	C	±0.04mm	250	5	11	16	30	1