

PCE Americas Inc.
711 Commerce Way
Suite 8
Jupiter
FL-33458
USA
From outside US: +1
Tel: (561) 320-9162
Fax: (561) 320-9176
info@pce-americas.com

PCE Instruments UK Ltd.
Units 12/13
Southpoint Business Park
Ensign way
Hampshire / Southampton
United Kingdom, SO31 4RF
From outside UK: +44
Tel: (0) 2380 98703 0
Fax: (0) 2380 98703 9
info@pce-instruments.com

www.pce-instruments.com/english
www.pce-instruments.com

Datasheet Moisture Analyser PCE-HMM 25 / 50 / 100 / 270

Technical Specification on the Universal Moisture Meter

Measuring ranges	Wood: 1 ... 75 % Material: 0.1 ... 2.4 % Temperature: -40 °C ... +70 °C / -40 ... +158 °F Humidity: 0 ... 100 %
Resolution	0.1 %
Accuracies	Wood: 1 ... 30 % / ±1 % 31 ... 60 % / ±2 % 61 ... 75 % / ±4 % Materials: ±0.5 % Temperature: -40 ... -10 °C, +40 ... +70 °C / ±2 °C -10 ... +40 °C / ±1 °C Humidity: 0 ... 20 %, 80 ... 100 % / ±5 % 20 ... 80 % / ±3.5 %
Electrode length	8 mm (internal), 30 mm and 150 mm (external)
Measuring principle	electrical resistance
Automatic turning-off function	after about 3 minutes (without using)
Automatic turning-off function (Display)	after about 10 seconds (without using)
Enclosure	Plastic, impact resistant
Battery	3 x CR 2032
Surrounding conditions	0 ... +40 °C, 0 ... 85 % RH
Measures	139 x 47 x 25 mm
Weight	100g (without electrode)