

96


Soldering Pot



- Temperature can be adjusted just by turning a knob during operation.

Features

Dimensions of Solder Pot



Operation



Packing List

96, 96-1	Unit, Spatula, Instruction manual
----------	-----------------------------------

Specifications

Part No.	96	96-1
Power consumption	200 W	
Dimensions	135 (W) × 105 (H) × 224 (D) mm	135 (W) × 120 (H) × 224 (D) mm
Weight*	1.5 kg	1.6 kg
Temperature range	100 to 450°C	100 to 380°C
Dimensions of solder pot	50 (W) × 54 (H) × 50 (D) mm	70 (W) × 64 (H) × 70 (D) mm
Molten solder capacity	0.85 kg	1.2 kg

* Without cord


485

Flow Soldering System



- Compatible with lead-free solder
- The impeller and chamber, which are the parts that corrode most easily, are plated with corrosion-resistant material.
- Both temperature and time are used to control the solder flow.

Dimensions



Packing List

485

Main unit, Air unit, Lamp (10 W [6 V]), Horizontal gauge, Spatula, IC tweezers, Waste collector, Positioning board, Foot switch, Locator light, Anti-oxidizer, 42-pin nozzle, 28-pin nozzle, 18/20-pin nozzle, 14/16-pin nozzle, 42-pin air hood, 28-pin air hood, 18/20-pin air hood, 14/16-pin air hood, Instruction manual

Specifications

Model No.	485
Power consumption	850 W
Temperature range	Room temperature to 300°C
Molten solder capacity	10 kg
Dimensions	500 (W) × 245 (H) × 550 (D) mm
Weight*	35 kg

Air unit

Air pressure	196 to 686 kPa (2 to 7 kgf/cm ²)
Dimensions	150 (W) × 100 (H) × 300 (D) mm
Weight**	3.5 kg

* Without solder and cord

** Without cord

* Solder is not included.