

SIPLUS HMI KTP700 Basic DP -20...+50°C with conformal coating based on 6AV2123-2GA03-0AX0 . Key/touch "operation, ""7"" TFT display," 65536 colors, PROFIBUS interface, configurable as of WinCC Basic V13/STEP 7 Basic V13, contains open source software, which is provided free of charge See enclosed CD-ROM



Figure similar

| General information   |  |
|---|--|
| Product type designation  | KTP700 Basic color DP                    |
| Display   |  |
| Design of display   | TFT widescreen display, LED backlighting |
| Screen diagonal   | 7 in                                     |
| Display width   | 154.1 mm                                 |
| Display height  | 85.9 mm                                  |
| Number of colors  | 65 536                                   |
| Resolution (pixels)   |  |
| • Horizontal image resolution   | 800 pixel                                |
| • Vertical image resolution   | 480 pixel                                |
| Backlighting  |  |
| • MTBF backlighting (at 25 °C)  | 20 000 h                                 |
| • Backlight dimmable  | Yes                                      |
| Control elements  |  |
| Keyboard fonts  |  |
| • Function keys   |  |
| — Number of function keys   | 8  |
| — Number of function keys with LEDs                                   | 0  |
| • Keys with LED   | No                                       |
| • System keys   | No                                       |
| • Numeric keyboard  | Yes; Onscreen keyboard                   |
| • alphanumeric keyboard   | Yes; Onscreen keyboard                   |
| Touch operation   |  |
| • Design as touch screen  | Yes                                      |
| Installation type/mounting  |  |
| Mounting in portrait format possible                                  | Yes                                      |
| Mounting in landscape format possible                                 | Yes                                      |
| maximum permissible angle of inclination without external ventilation | 35°                                      |
| Supply voltage  |  |
| Type of supply voltage  | DC                                       |
| Rated value (DC)  | 24 V                                     |
| permissible range, lower limit (DC)                                   | 19.2 V                                   |
| permissible range, upper limit (DC)                                   | 28.8 V                                   |
| Input current   |  |


|  |   |
|--|---|
| Current consumption (rated value)                | 230 mA                                  |
| Starting current inrush I <sup>2</sup> t         | 0.2 A <sup>2</sup> ·s                   |
| <b>Power</b>                                     |   |
| Active power input, typ.                         | 5.5 W                                   |
| <b>Processor</b>                                 |   |
| Processor type                                   | ARM                                     |
| <b>Memory</b>                                    |   |
| Flash  | Yes                                     |
| RAM  | Yes                                     |
| Memory available for user data                   | 10 Mbyte                                |
| <b>Type of output</b>                            |   |
| Acoustics  |   |
| • Buzzer   | Yes                                     |
| • Speaker  | No                                      |
| <b>Time of day</b>                               |   |
| Clock  |   |
| • Hardware clock (real-time)                     | Yes                                     |
| • Software clock                                 | Yes                                     |
| • retentive                                      | Yes; Back-up duration typically 6 weeks |
| • synchronizable                                 | Yes                                     |
| <b>Interfaces</b>                                |   |
| Number of industrial Ethernet interfaces         | 0                                       |
| Number of RS 485 interfaces                      | 1                                       |
| Number of RS 422 interfaces                      | 1; together with RS 485                 |
| Number of RS 232 interfaces                      | 0; with optional adapter                |
| Number of USB interfaces                         | 1; Up to 16 GB                          |
| Number of 20 mA interfaces (TTY)                 | 0                                       |
| Number of parallel interfaces                    | 0                                       |
| Number of other interfaces                       | 0                                       |
| Number of SD card slots                          | 0                                       |
| With software interfaces                         | No                                      |
| <b>Industrial Ethernet</b>                       |   |
| • Industrial Ethernet status LED                 | 0                                       |
| <b>Protocols</b>                                 |   |
| PROFINET   | No                                      |
| Supports protocol for PROFINET IO                | No                                      |
| IRT  | No                                      |
| PROFIBUS   | Yes                                     |
| EtherNet/IP                                      | No                                      |
| MPI  | Yes                                     |
| <b>Protocols (Ethernet)</b>                      |   |
| • TCP/IP   | No                                      |
| • DHCP   | No                                      |
| • SNMP   | No                                      |
| • DCP  | No                                      |
| • LLDP   | No                                      |
| <b>WEB characteristics</b>                       |   |
| • HTTP   | No                                      |
| • HTML   | No                                      |
| <b>Redundancy mode</b>                           |   |
| Media redundancy                                 |   |
| — MRP  | No                                      |
| <b>Further protocols</b>                         |   |
| • CAN  | No                                      |
| • MODBUS   | Yes; Modicon (MODBUS RTU)               |
| <b>Interrupts/diagnostics/status information</b> |   |
| Diagnoses  |   |

|  |   |
|--|---|
| • Diagnostic information readable  | No  |
| <b>EMC</b>   |   |
| Emission of radio interference acc. to EN 55 011   |   |
| • Limit class A, for use in industrial areas   | Yes   |
| • Limit class B, for use in residential areas  | No  |
| <b>Degree and class of protection</b>  |   |
| NEMA (front)   |   |
| • Enclosure Type 4 at the front  | Yes   |
| • Enclosure Type 4x at the front   | Yes   |
| <b>Ambient conditions</b>  |   |
| Suited for indoor use  | Yes   |
| Suited for outdoor use   | No  |
| Ambient temperature during operation   |   |
| Operation (vertical installation)  |   |
| — For vertical installation, min.  | -20 °C; = Tmin  |
| — For vertical installation, max.  | 50 °C   |
| Operation (max. tilt angle)  |   |
| — At maximum tilt angle, min.  | -20 °C; = Tmin  |
| — At maximum tilt angle, min.  | 40 °C   |
| Operation (vertical installation, portrait format)   |   |
| — For vertical installation, min.  | -20 °C; = Tmin  |
| — For vertical installation, max.  | 40 °C   |
| Operation (max. tilt angle, portrait format)   |   |
| — At maximum tilt angle, min.  | -20 °C; = Tmin  |
| — At maximum tilt angle, min.  | 35 °C   |
| Ambient temperature during storage/transportation  |   |
| • min.   | -20 °C  |
| • max.   | 60 °C   |
| Altitude during operation relating to sea level  |   |
| • Installation altitude above sea level, max.  | 5 000 m   |
| • Ambient air temperature-barometric pressure-altitude                                       | Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m) // Tmin ... (Tmax - 10 K) at 795 hPa ... 658 hPa (+2 000 m ... +3 500 m) // Tmin ... (Tmax -20 K) at 658 hPa ... 540 hPa (+3 500 m ... +5 000 m) |
| Relative humidity  |   |
| • With condensation, tested in accordance with IEC 60068-2-38, max.                          | 100 %; RH incl. condensation/frost (no commissioning when condensation present), vertical mounting position   |
| Resistance   |   |
| Coolants and lubricants  |   |
| — Resistant to commercially available coolants and lubricants                                | Yes; Incl. diesel and oil droplets in the air   |
| Use in stationary industrial systems   |   |
| — to biologically active substances according to EN 60721-3-3                                | Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna); Class 3B3 on request  |
| — to chemically active substances according to EN 60721-3-3                                  | Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *  |
| — to mechanically active substances according to EN 60721-3-3                                | Yes; Class 3S4 incl. sand, dust, *  |
| Use on ships/at sea  |   |
| — to biologically active substances according to EN 60721-3-6                                | Yes; Class 6B2 mold and fungal spores (excluding fauna); Class 6B3 on request   |
| — to chemically active substances according to EN 60721-3-6                                  | Yes; Class 6C3 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *  |
| — to mechanically active substances according to EN 60721-3-6                                | Yes; Class 6S3 incl. sand, dust; *  |
| Usage in industrial process technology   |   |
| — Against chemically active substances acc. to EN 60654-4                                    | Yes; Class 3 (excluding trichlorethylene)   |
| — Environmental conditions for process, measuring and control systems acc. to ANSI/ISA-71.04 | Yes; Level GX group A/B (excluding trichlorethylene; harmful gas concentrations up to the limits of EN 60721-3-3 class 3C4 permissible); level LC3 (salt spray) and level LB3 (oil)                             |
| Remark   |   |

|   |   |
|---|---|
| — Note regarding classification of environmental conditions acc. to EN 60721, EN 60654-4 and ANSI/ISA-71.04   | * The supplied plug covers must remain in place over the unused interfaces during operation!  |
| <b>Conformal coating</b>  |   |
| <ul style="list-style-type: none"> <li>• Coatings for printed circuit board assemblies acc. to EN 61086</li> <li>• Protection against fouling acc. to EN 60664-3</li> <li>• Military testing according to MIL-I-46058C, Amendment 7</li> <li>• Qualification and Performance of Electrical Insulating Compound for Printed Board Assemblies according to IPC-CC-830A</li> </ul>   | <p>Yes; Class 2 for high reliability</p> <p>Yes; Type 1 protection</p> <p>Yes; Discoloration of coating possible during service life</p> <p>Yes; Conformal coating, Class A</p>   |
| <b>Operating systems</b>  |   |
| proprietary   | Yes   |
| <b>pre-installed operating system</b>   |   |
| <ul style="list-style-type: none"> <li>• Windows CE</li> </ul>  | No  |
| <b>Configuration</b>  |   |
| Message indicator   | Yes   |
| Alarm system (incl. buffer and acknowledgment)  | Yes   |
| Process value display (output)  | Yes   |
| Process value default (input) possible  | Yes   |
| Recipe management   | Yes   |
| <b>Configuration software</b>   |   |
| <ul style="list-style-type: none"> <li>• STEP 7 Basic (TIA Portal)</li> <li>• STEP 7 Professional (TIA Portal)</li> <li>• WinCC flexible Compact</li> <li>• WinCC flexible Standard</li> <li>• WinCC flexible Advanced</li> <li>• WinCC Basic (TIA Portal)</li> <li>• WinCC Comfort (TIA Portal)</li> <li>• WinCC Advanced (TIA Portal)</li> <li>• WinCC Professional (TIA Portal)</li> </ul>   | <p>Yes; via integrated WinCC Basic (TIA Portal)</p> <p>Yes; via integrated WinCC Basic (TIA Portal)</p> <p>No</p> <p>No</p> <p>No</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> |
| <b>Languages</b>  |   |
| <b>Online languages</b>   |   |
| <ul style="list-style-type: none"> <li>• Number of online/runtime languages</li> </ul>  | 10  |
| <b>Project languages</b>  |   |
| <ul style="list-style-type: none"> <li>• Languages per project</li> </ul>   | 32  |
| <b>Functionality under WinCC (TIA Portal)</b>   |   |
| Libraries   | Yes   |
| <b>Applications/options</b>   |   |
| <ul style="list-style-type: none"> <li>• Web browser</li> </ul>   | Yes   |
| Number of Visual Basic Scripts  | No  |
| <b>Task planner</b>   |   |
| <ul style="list-style-type: none"> <li>• time-controlled</li> <li>• task-controlled</li> </ul>  | <p>No</p> <p>Yes</p>  |
| <b>Help system</b>  |   |
| <ul style="list-style-type: none"> <li>• Number of characters per info text</li> </ul>  | 500   |
| <b>Message system</b>   |   |
| <ul style="list-style-type: none"> <li>• Number of alarm classes</li> <li>• Bit messages <ul style="list-style-type: none"> <li>— Number of bit messages</li> </ul> </li> <li>• Analog messages <ul style="list-style-type: none"> <li>— Number of analog messages</li> </ul> </li> <li>• S7 alarm number procedure</li> <li>• System messages HMI</li> <li>• System messages, other (SIMATIC S7, Sinumerik, Simotion, etc.)</li> <li>• Number of characters per message</li> <li>• Number of process values per message</li> </ul> | <p>32</p> <p>1 000</p> <p>25</p> <p>No</p> <p>Yes</p> <p>Yes; System message buffer of the SIMATIC S7-1200 and S7-1500</p> <p>80</p> <p>8</p>                                     |

|  |   |
|--|---|
| • Acknowledgment groups                | Yes   |
| • Message indicator                    | Yes   |
| • Message buffer                       |   |
| — Number of entries                    | 256   |
| — Circulating buffer                   | Yes   |
| — retentive                            | Yes   |
| — maintenance-free                     | Yes   |
| <b>Recipe management</b>               |   |
| • Number of recipes                    | 50  |
| • Data records per recipe              | 100   |
| • Entries per data record              | 100   |
| • Size of internal recipe memory       | 256 kbyte   |
| • Recipe memory expandable             | No  |
| <b>Variables</b>                       |   |
| • Number of variables per device       | 800   |
| • Number of variables per screen       | 100   |
| • Limit values                         | Yes   |
| • Multiplexing                         | Yes   |
| • Structures                           | No  |
| • Arrays                               | Yes   |
| <b>Images</b>                          |   |
| • Number of configurable images        | 250   |
| • Permanent window/default             | Yes   |
| • Global image                         | Yes   |
| • Image selection by PLC               | Yes   |
| • Image number in the PLC              | Yes   |
| <b>Image objects</b>                   |   |
| • Number of objects per image          | 100   |
| • Text fields                          | Yes   |
| • I/O fields                           | Yes   |
| • Graphic I/O fields (graphics list)   | Yes   |
| • Symbolic I/O fields (text list)      | Yes   |
| • Date/time fields                     | Yes   |
| • Switches                             | Yes   |
| • Buttons                              | Yes   |
| • Graphic display                      | Yes   |
| • Icons                                | Yes   |
| • Geometric objects                    | Yes   |
| <b>Complex image objects</b>           |   |
| • Number of complex objects per screen | 10  |
| • Alarm view                           | Yes   |
| • Trend view                           | Yes   |
| • User view                            | Yes   |
| • Status/control                       | No  |
| • Sm@rtClient view                     | No  |
| • Recipe view                          | Yes   |
| • f(x) trend view                      | No  |
| • System diagnostics view              | Yes; System message buffer of the SIMATIC S7-1200 and S7-1500 |
| • Media Player                         | No  |
| • Bar graphs                           | Yes   |
| • Sliders                              | No  |
| • Pointer instruments                  | No  |
| • Analog/digital clock                 | No  |
| <b>Lists</b>                           |   |
| • Number of text lists per project     | 300   |
| • Number of entries per text list      | 100   |
| • Number of graphics lists per project | 100   |
| • Number of entries per graphics list  | 100   |

| Archiving  |                            |
|--|----------------------------|
| • Number of archives per device                        | 2                          |
| • Number of entries per archive                        | 10 000                     |
| • Message archive                                      | Yes                        |
| • Process value archive                                | Yes                        |
| • Archiving methods                                    |                            |
| — Sequential archive                                   | Yes                        |
| — Short-term archive                                   | Yes                        |
| • Memory location                                      |                            |
| — Memory card  | No                         |
| — USB memory   | Yes                        |
| — Ethernet   | No                         |
| • Data storage format                                  |                            |
| — CSV  | No                         |
| — TXT  | Yes                        |
| — RDB  | No                         |
| Security   |                            |
| • Number of user groups                                | 50                         |
| • Number of user rights                                | 32                         |
| • Number of users                                      | 50                         |
| • Password export/import                               | Yes                        |
| • SIMATIC Logon  | No                         |
| Character sets   |                            |
| • Keyboard fonts                                       |                            |
| — US English   | Yes                        |
| Transfer (upload/download)                             |                            |
| • MPI/PROFIBUS DP                                      | Yes                        |
| • USB  | No                         |
| • Ethernet   | No                         |
| • using external storage medium                        | No                         |
| Process coupling                                       |                            |
| • S7-1200  | Yes                        |
| • S7-1500  | Yes                        |
| • S7-200   | Yes                        |
| • S7-300/400   | Yes                        |
| • LOGO!  | Yes                        |
| • WinAC  | Yes                        |
| • SINUMERIK  | Yes; No access to NCK data |
| • SIMOTION   | Yes                        |
| • Allen Bradley (EtherNet/IP)                          | No                         |
| • Allen Bradley (DF1)                                  | Yes                        |
| • Mitsubishi (MC TCP/IP)                               | No                         |
| • Mitsubishi (FX)                                      | Yes                        |
| • OMRON (FINS TCP)                                     | No                         |
| • OMRON (LINK/Multilink)                               | Yes                        |
| • Modicon (Modbus TCP/IP)                              | No                         |
| • Modicon (Modbus)                                     | Yes                        |
| Service tools/configuration aids                       |                            |
| • Backup/Restore manually                              | Yes                        |
| • Backup/Restore automatically                         | No                         |
| • Simulation   | Yes                        |
| • Device switchover                                    | Yes                        |
| Peripherals/Options                                    |                            |
| Printer  | No                         |
| SIMATIC HMI MM memory card: Multi Media Card           | No                         |
| SIMATIC HMI SD memory card: Secure Digital memory card | No                         |
| USB memory   | Yes                        |

| Mechanics/material   |  |
|--|--|
| Enclosure material (front)   |  |
| <ul style="list-style-type: none"> <li>• Plastic</li> <li>• Aluminum</li> <li>• Stainless steel</li> </ul> | Yes<br>No<br>No  |
| Dimensions   |  |
| Width of the housing front   | 214 mm   |
| Height of housing front  | 158 mm   |
| Mounting cutout, width   | 197 mm   |
| Mounting cutout, height  | 141 mm   |
| Overall depth  | 39 mm  |
| Weights  |  |
| Weight without packaging   | 800 g  |
| Weight incl. packaging   | 1 kg   |
| <b>last modified:</b>  | 3/2/2021  |