

Digital Concrete Testing Hammer Reinforcement Bar Position Tester



Product Details:

Place of Origin: **Beijing**

Brand Name: **HUATEC**

Certification: **CE ISO**

Model Number: **HLT210+**

Payment & Shipping Terms:

Minimum Order Quantity: **1 set**

Packaging Details: **carton**

Delivery Time: **3 days**

Payment Terms: **T/T, Western Union, L/C**

Supply Ability: **300 per months**

Large Image : [Digital Concrete Testing Hammer Reinforcement Bar Position Tester](#)



[Chat Now](#)

Detailed Product Description

Investigation Depth:	180mm	Rebar Diameter Range(mm):	Φ6-Φ50
Cover Thickness Range First Range:	6-90mm	Cover Thickness Range Second Range:	7-180mm
Power Source Alkaline CellX6:	>30 Hours		

Digital Concrete Testing Hammer Reinforcement Bar Position Tester

Features

- investigation depth could reach 180mm

- Single comprehensive probe. No need to replace during test.
- back-lit screen let instrument can be normal used under the condition of insufficient light
- Machine software is complete .The report could be printed automatically connecting with computer

No strong alternating electromagnetic field

No corrosive gas in the air.

Avoid larger vibration and impact

Avoid the LCD panel contact with sunlight directly

Product usage

Testing concrete cover thickness

Test concrete member internal reinforcement position, rebar spacing, reinforcement position distribution.

Estimation bar diameter

Detection of Cable and Plumbing pipe

Specifications		
Rebar diameter range(mm) :Φ6-Φ50		
Maximum error of cover thickness +/- 1		
Cover thickness range(mm)		
First range(mm) 6-90		
Second range(mm) 7-180		
Maximum error of cover thickness		
First range(mm) Second range(mm)		
6-59	7-79	+/- 1
60-69	80-119	+/- 2
70-90	120-180	+/- 4

Environmental requirement
Working temperature°C -10~40°C
Relative humidity <90%
Power source Alkaline cellX6, >30 hours

Standard Accessories	1. software disc
	2. manual
	3. approval certificate
	4. baldric
	5. suitcase

