Drill Hole ϕ 6mm Compact and lightweight. Equipped with adjust-valve and silencer, which offer comfort to operators



Drill Hole ϕ 8mm Compact, lightweight, and noise reducer equipped, for comfort to the workplace.



Drill Hole \$\phi\$ 10mm Compact, lightweight, and noise reducer equipped, for comfort to the workplace.



Model No.	Steel Plate Drilling Capacity φ (mm)	No Load Speed (rpm)	Air Consumption (m²/min)	Hose Coupling	Air Hose Inner Dia. (mm)	Overall Length (mm)	Weight (g)	Chuck Size (mm)	Accessories Plug	EDP No.
GT-D60-30	6	3,000	0.52	Rc 1/4	6.35	188	880	6.0	BPB-2 Chuck handle	310603
GT-D60-45	6	4,500	0.56	Rc 1/4	6.35	188	890	6.0	BPB-2 Chuck handle	310603
GT-CD60-34	6	3,400	0.42	Rc 1/4	6.35	250	820	6.0	BPB-2 Lock Offset handle, wrench	336141
GT-CD60-34L	6	3,400	0.42	Rc 1/4	6.35	251	840	6.0	BPB-2 Lock Offset handle, wrench	336142
GT-D80-20	8	2,000	0.35	Rc 1/4	6.35	165	940	8.0	BPB-2 Chuck handle	310604
GT-D80-20K	8	2,000	0.35	Rc 1/4	6.35	171	960	8.0	BPB-2 -	310605
GT-D100-15	10	1,500	0.54	Rc 1/4	6.35	189	1,280	10.0	BPB-2 Chuck handle	310606
GT-D100-15K	10	1,500	0.54	Rc 1/4	6.35	195	1,300	10.0	BPB-2 -	310607

[·]Working air pressure: 0.6MPa ·Overall length and Weight: Accessories not included.