

PCE Americas Inc. 711 Commerce Way Suite 8 Jupiter FL-33458 USA From outside US: +1 Tel: (561) 320-9162 Fax: (561) 320-9176 info@pce-americas.com PCE Instruments UK Ltd. Units 12/13 Southpoint Business Park Ensign way Hampshire / Southampton United Kingdom, SO31 4RF From outside UK: +44 Tel: (0) 2380 98703 9 Fax: (0) 2380 98703 9 info@pce-instruments.com

www.pce-instruments.com/english www.pce-instruments.com

digital Concrete tester HT 224E

Hardness Tester PCE-HT 224E with Digital Display

Mechanical concrete hardness tester with OLED / Measuring range 10 ... 100 N (2.2 ... 22.5 lbs) mm² / Data storage analysis software / Built-in battery for mobile use / Test load 2.207 J / For measuring the quality of concrete surfaces

The hardness tester is a measuring tool for testing the strength of concrete. The hardness tester is measured according to the Schmidt principle. According to this measurement method, the quality of concrete can be measured with the hardness tester. Thus, the hardness tester finds its essential application in the construction and in the construction sector. The built-in mechanism on the hardness tester always ensures the same impact energy of 2.207 Nm.

In addition to testing concrete, the hardness tester can also store measured data. The stored measurement data can be transferred from the hardness tester to a PC after a measurement run. For this, the mini-USB interface is available on the hardness tester. The evaluation of the measurements from the hardness tester is carried out with the supplied PC software.

- OLED for reading the measured values
- USB interface for connection to a PC
- Measuring range 10 ... 100 N / 2.2 ... 22.5 lbs / mm²
- Measurement of the hardness of concrete
- Data storage for later analysis
- Rechargeable battery for mobile use

Specifications:

10 100 N / 2.2 22.5 lbs / mm ²
$\pm 0.1 \text{ R}$
OLED
2.207 Nm, 0.225 kgm
Bluetooth, micro USB
1,000 data units with 256 measurements each
-40 60°C / -40 140°F
3.7V Li-ion battery
Primary: 100 240V AC, 50/60 Hz
Secondary: 5V DC, 1 A
280 x 75 x 60 mm / 11 x 3 x 2.4 in
About 1.2 kg / 2.6 lbs

Delivery scope:

x Hardness tester PCE-HT 224E
x Mini USB cable
x Emery stone
x Software CD
x Charger
x Transport case
x User manual