Industrial Ultrasonic Cleaner Series (KS series)

- Use tap water, alcohol, organic solvent, etc.as cleaning fluid.
- Industrial-grade high power transducer for superior cleaning result, obvious cleaning effect can be seen with naked eyes.
- Top quality SUS304 stainless steel made for inner tank, housing and cover.
- Separated ultrasonic generator with adjustable ultrasonic power (presence ultrasonic generator depends on model).
- Time setting with 1-99 minutes or 1-30 minutes (depends on model).
- Built-in heating system reach to max 110°C.
- With SUS material cleaning basket (optional).



→ Used in shop/store/factory

(clean jewelry, glass, fruit and vegetables, PCB board, computer mainboard and components, hardware, screw and nut, bullet shell, etc. in large batch)

→ Used in laboratory field (clean test tube, beaker, glassware, other lab apparatus)

Used in medical and dental clinic (dental hand piece, dental needle, dental drill, false tooth, forceps, other dental and medical instruments)

→ Used in industrial field

(clean engine parts, injector, air cylinder, mould, blind window, anilox roller, mesh sieve, golf balls,etc.)

Customization (tank size, material or frequency) is available for this series.

Model No.		KS-1006	KS-1012	KS-1018	KS-1024	KS-1030	KS-1036
Inner Tank Dimension (MM)	L	305	355	406	500	500	500
	W	250	305	305	355	406	460
	Н	305	355	460	500	500	550
External Dimension (MM)		485	535	586	680	680	680
			485	485		586	640
				680			
Tank Capacity		23L	38L	56L	88L	101L	126L
Tank Material		SUS304					
Ultrasonic Frequency		28KHz or 40KHz					
Transducer Qty		6PCS	12PCS	18PCS	24PCS	30PCS	36PCS
Ultrasonic Power-Max		300W	600W	900W	1200W	1500W	1800W
Heating power -Max							
Separated Ultrasonic Generator(YES or NO)		NO (all-in-one)					
Heating Power Supply		AC 220V/240V, 1, 20AMP AC380V,3+N,20AMP					
Generator Power Supply		AC 220V/240V,1, 20AMP					

