

YIHUA 1502DD LED dc power supply



Product Details

 This power supply is for cell phone/computer maintenance work and is a specifically designed, all-function, power supply appliance.
Dual LED displays to show current and voltage. High-performance mobile phone repair equipment that is both affordable and easy to operate. 3. Comes with a 0-15V DC output function (the voltage output can be adjusted both by gears or a slide controller).

- 4. A two power settings: adjustable throughout 0.6A-2A range.
- 5. Short circuit protection and automatic recovery function
- 6. Current: 0-2A with direct output levels of 1.5V, 3.6V, 4.8V, 6.0V or 7.2V.

Parameters

Parameters	
Rated voltage	AC220V±10% 50Hz
Power of complete machine	15W
Operating environment	$0{\sim}40^{\circ}$ C relative humidity \leq 80%
Storage temperature	$-20{\sim}80^\circ$ C relative humidity ${<}80\%$
Dimensions of the machine b ody	17*21*16.5cm
Weight	1.06KG
Performance parameters	
Output voltage	Adjustable continuously within 0 ~ 15V
Output current	Adjustable continuously within 0 ~ 1A (current limitation adjustment when above 0.2A)
Output power	15W
Source effect	≤1mV
Load effect	≤0.33%
Ripple noise	≤3mVrms (5Hz ~ 1MHz) /≤3mArms
Display accuracy	0.1V/0.1A/1mA
Protection mode	Over-current, short circuit, over-
	temperature protection

