

1700°C / 1800°C Furnace



Package Model		FU-PK-S1	FU-PK-S2	FU-PK-S3	FU-PK-S4
Furnace Model		SH-FU-50TS-WG	SH-FU-80TS-WG	SH-FU-100TS-WG	SH-FU-120TS-WG
Chiller		SH-WB-13CDR	SH-WB-13CDR	SH-WB-22CDR	SH-WB-48CDR
Vacuum Pump		SH-V10	SH-V10	SH-V10	SH-V10
Oil Mist Trap		VOT-1020	VOT-1020	VOT-1020	VOT-1020
Dimension (Frame)		1265x725x1885mm	1265x725x1915mm	1265x800x1970mm	1265x800x2050mm
		49.80x28.54x74.21"	49.80x28.54x75.39"	49.80x31.49x77.56"	49.80x31.49x80.71"
Cat.NO	Max 1700°C	FUPKS1300-17	FUPKS2300-17	FUPKS3300-17	FUPKS4300-17
	Max 1800°C	FUPKS1300-18	FUPKS2300-18	FUPKS3300-18	FUPKS4300-18

Cooling Chiller



This is unit to supply coolant to cooling line.

Model	Bath Capacity	Temp Range
SH-WB-7CDR	7 L	-20°C~150°C
SH-WB-13CDR	13 L	
SH-WB-22CDR	22 L	
SH-WB-48CDR	48 L	-20°C~65°C

Vacuum pump



Oil rotary and head direct connection type. Feature of this type is convenient to operate and move because of it's small size and light weight.

Model	Pump Speed
SH-V10	78L/Min
SH-V20	156L/Min
SH-V40	312L/Min
SH-V60	474L/Min