DIGITAL ANGLE TORQUE WRENCH



- Clockwise and counter-clockwise operation
- Set the desired torque first. After reaching the desired torque, set the angle and turn the wrench at this angle to apply extra torque
- Unit: N.m, in.lb, ft.lb, kg.cm, degree
- Peak and track working mode
- Target torque or angle value can be set, with audible and visible alarm: green LED light on and buzzer sounds when torque or angle value is 90%~100% of target torque or angle both green and red LED light on and buzzer sounds when target torque or angle value is reached
- Power off in 5 minutes automatically
- Non-slip grip handle
- With damp record
- With overload record (once the torque reaches 110% of the maximum range)
- Supplied with calibration certificate



Set the desired torque first. After reaching the desired torque, set the angle and turn the wrench at this angle to apply extra torque

SPECIFICATION

Code		IST-1W30A	IST-1W135A	IST-1W200A	IST-1W340A
Range	torque	6~30N.m	27~135N.m	40~200N.m	68~340N.m
	angle	0~999°			
Accuracy	clockwise	±2%			
	counter-clock wise	±3%			
	angle	±2° (rotate 90°)			
Resolution	torque	0.01N.m	0.1N.m	0.1N.m	0.1N.m
	angle	1°			
Square driver (L)		1/4"	3/8"	1/2"	1/2"
Powersupply		2xAA batteries, for 110 hours working			
Length		390mm	415mm	530mm	650mm
Weight		830g	950g	1400g	1600g

OPTIONAL ACCESSORY

Calibration cable	IST-1W-CABLE
-------------------	--------------

