

Humidity Temp. Meter

TES-1260 Humidity Temperature Meter



Features

- ◆ Slimline and Stylish
 - ◆ Large Dual LCD display
 - ◆ Dew Point Reading / Wet Bulb Reading
 - ◆ MAX/MIN with Time Stamp
 - ◆ Data Hold function
 - ◆ °C/°F Switchable
 - ◆ Data memory and read function (99 readings from LCD display)
 - ◆ Auto Power Off
- **Range:**
Temperature: -20°C~60°C (-4°F~140°F)
Humidity: 1%RH ~ 99%RH
 - **Resolution:** 0.1°C/0.1°F/0.1%RH
 - **Accuracy:**
Temperature: ± 0.5°C, ± 0.9°F
Humidity: ± 3%RH (at 25°C, 30~99%RH)
± 5%RH (at 25°C, 1~30%RH)
 - **Data Memory Capacity:**
99 sets reading from LCD display

TES-1360A Humidity/Temperature Meter Features



Features

- ◆ Ideal for: Laboratory, Quality Control, Air Conditioning & Process Engineering
 - ◆ Instant performance of Humidity measurement by Precision thin-film capacitance sensor.
 - ◆ High Resolution of 0.1% R.H., 0.1°C & 0.1°F
 - ◆ Data Hold function to hold the LCD reading.
 - ◆ Data memory and read function (99 sets)
- **Range:**
Humidity: 10%~95% R.H.
Temperature: -20°C~+60°C / -4°F~+140°F
Resolution: 0.1% R.H. 0.1°C, 0.1°F
 - **Accuracy (after calibration)**
Humidity: ± 3% R.H.
Temperature: ± 0.8°C, ± 1.5°F
 - **Auxiliary outputs:**
Humidity: 10mV DC/1% R.H.
Temperature: 10mV DC/1°C, 10mV DC/1°F

TES-1361C Datalogging Humidity/Temperature Meter



Features

- ◆ Logging 7000 dual Reading (RH% & Temp) with Data/Time Stamp
 - ◆ Switchable Main display & Secondary display
 - ◆ Dual display with time clock
 - ◆ Accurate & Easy Operation
 - ◆ RS-232 interface (software included)
- **Range:**
Humidity: 10%...95%R.H.
Temperature: -20°C~+60°C/-4°F ~+140°F
 - **Accuracy:**
Humidity: ± 3%R.H. (at 25°C, 30~95%R.H.)
Temperature: ± 0.8°C, ± 1.5°F
 - **Record:** (Data logging)
7000 Point Data logger (Dual Data)