

### TES-1362 Printing Humidity/Temperature Meter



#### Features

- ◆ Triple LCD Display for RH% Humidity, T1 for air, T2 for Type K
- ◆ Dew Point Reading
- ◆ Max/Min/Data Hold
- ◆ Real Time Stamp
- ◆ Periodically Print out from Pre-Set time interval
- **Range:**  
T1: Temp.: -20°C~60°C (-4°F~140°F) / (± 0.8°C, ± 1.5°F)  
Humidity: 10%RH~95%RH (± 3%RH)  
T2: Type K: -200°C~1333°C (-58°F~2431°F) / (0.1%rdg + 0.8°C)
- **Resolution:** 0.1°C/0.1°F/0.1%RH
- **Sampling Rate:** 1 time/sec.

### TES-1364/1365 Datalogging Humidity/Temperature Meter



#### Features

- ◆ Data Hold & Relative function
- ◆ Dual LCD display with Bargraph indication
- ◆ Dew Point Reading & Wet Bulb Reading
- ◆ MAX/MIN with Time Stamp
- ◆ Data Memory and Read function (99 readings from LCD display)
- ◆ Datalogging capacity 15,000 dual reading (%RH & Temp-TES-1365)
- ◆ RS-232 Interface & window software (TES-1365)
- ◆ Automatic Timer Recording for Datalogger(TES-1365)
- **Range:**  
Temperature:-20°C~60°C(-4°F~140°F)  
Humidity: 10%RH~95%RH
- **Resolution:** 0.1°C/0.1°F/0.1% RH
- **Accuracy:**  
Temperature : ± 0.5°C, ± 0.9°F  
Humidity:  
± 3%RH(at 25°C30~95%RH)  
± 5%RH(at 25°C10~30%RH)
- **Datalogging:** (TES-1365)  
Continues Recorder: 15,000 data sets.

## Leakage Current Tester

### CM-03 Leakage Current Tester



#### Features

- ◆ 10uA Ultra High Resolution on 40mA range
- ◆ 30mm Large Conductor Diameter
- ◆ ACA 5 Range (40mA, 400mA, 4A, 40A, 60A)
- ◆ Fast bargraph display (30 times/sec.)
- ◆ Max/Min, Data Hold function
- ◆ Relative measurement
- **AC Current:**  
(± 1.0% rdg ± 3dpts)  
40m/400m/4A/40A/60A
- **AC Voltage:** 400V
- **Resistance and Continuity:** 40~400 Ω

CE U<sub>L</sub>  
IEC 1010  
CAT III 300V  
CAT II 600V