

ULTRASONIC THICKNESS GAGE CODE ISU-720D

PENETRATE NON-METALLIC COATING AND
MEASURE THE THICKNESS OF METAL SUBSTRATES

DATA
OUTPUT

WITH A AND B SCAN

- Two measuring modes, Echo-Echo (E-E) and Transmit-Echo (T-E):
 - E-E is applicable for non-metallic coating (such as paint, plastic resin, etc.) on metal substrates, can penetrate coating and measure the thickness of substrates
 - T-E is to measure the thickness of material without coating, such as metal, plastic, glass, nylon, resin, ceramics, ice, etc.
- A scan, through the waveform, judges whether there are impurities, pores, cracks and so on inside, in order to avoid wrong measurement
- B scan, measures continuously, displays the thickness change on the screen
- Transducers can be automatically identified and zeroed
- Memory 10000 measurement values and transmitted through USB cable
- Automatic or manual measurement
- When transducers are removed from workpieces, the measurement data are held on screen for easy viewing
- Set upper and lower limits for alarm when out-of-tolerance
- Automatic power off



SPECIFICATION

Measuring range	T-E mode: substrate thickness 1.5~200mm
	E-E mode: substrate thickness 3~25mm
Measuring unit	mm/inch
Resolution	0.1/0.01mm
Accuracy	±0.04mm (H<9.9mm)
	±(0.04+0.1%H)mm (H: 10~99.9mm)
	±(0.3%H)mm (H>100mm)
	H is the thickness to be measured in mm
Frequency	5.0MHZ
Display	320×240, color screen display
Velocity	1000~9999m/s
Measuring frequency	2 times/second and 10 times/second
Applicable temperature	-20~50°C
Output	USB
Power supply	2×1.5V AA batteries
Dimension	133×75×29mm
Weight	260g (Including batteries)




Couplant (included)




STANDARD DELIVERY

Main unit	1pc
Bicrystal transducer ISU-T07	1pc
Battery (AA)	2pcs
Couplant	1bottle
USB cable	1pc



Echo-Echo
mode (E-E)



Transmit-Echo
mode (T-E)

Transducer ISU-T04(**optional**)



Transducer ISU-T06(**optional**)



Transducer ISU-T08(**optional**)



Transducer ISU-T12(**optional**)



Transducer ISU-T13(**optional**)



Transducer ISU-T25(**optional**)



OPTIONAL ACCESSORY

Transducer	ISU-T04, ISU-T06, ISU-T08, ISU-T12, ISU-T13, ISU-T25
Couplant (for ISU-T13)	ISU-HT5-COUPPLANT

Code	Mode	Frequency	Diameter (Ød)	Measuring range	Minimum size of pipe for measurement (diameter × wall thickness)	Applicable temperature	Application
ISU-T07 (included)	T-E E-E	5.0MHz	13.2mm	T-E mode: 1.5~200mm E-E mode: 3~25mm	T-E mode: Φ25×3mm	<60°C	general use
ISU-T04(optional)	T-E	10.0MHz	6mm	0.7~20mm	Φ15×1mm	<60°C	for small tube
ISU-T06(optional)	T-E	7.5MHz	9mm	0.7~50mm	Φ15×1.2mm	<60°C	for thin material
ISU-T08(optional)	T-E	5.0MHz	11mm	0.8~300mm	Φ25×1.2mm	<60°C	general use
ISU-T12(optional)	T-E	2.0MHz	17mm	2~400mm	Φ40×3mm	<60°C	for casting iron
ISU-T13(optional)	T-E	5.0MHz	15mm	2~200mm	Φ25×2mm	<350°C	for high temperature
ISU-T25(optional)	T-E	1.0MHz	26mm	3~200mm	—	<60°C	for fiberglass and organic material