











XIAMEN TOB NEW ENERGY TECHNOLOGY CO., LTD.

Provide A Full Set Of Solutions For Battery Machines.

SALES tob.amy@tobmachine.com TECH SUPPORT +86-18120715609

Search...

Q



2L Laboratory Planetary Vacuum Mixer For Li-Ion Battery Slurry Mixing

vacuum planetary mixer for different lithium battery powder and liquid mixed and dispersed.

- Brand:TOB NEW ENERGY
- Item No.:TOB-XFZH02
- Order(Moq):1set
- Payment:L/C,T/T,Western Union, Paypal
- Product Origin:China
- Shipping Port:Xiamen
- Lead Time:30days

Product Detail

2L Laboratory Planetary Vacuum Mixer For Li-ion Battery Slurry Mixing

SPECIFICATIONS

- 1. Used for Different lithiumbattery powder and liquid mixed and dispersed, and finally a uniformly mixed battery slurry is obtained. Ideal for highly viscous processes.
- 2. Adapt to the working condition viscosity range ≤ 1.2 million cps.

Model	TOB-XFZH02			
Lower Barrel Parts				
Design total volume	3.8L			
Effective volume	1.2L-2L			
Container inner diameter	180mm			
Container inside depth	150mm			
Container material	Contact with material 304			
Tempering jacket form	Single-layer jacket for barrel wall for cooling or heating; single-layer jacket at the bottom of the barrel for cooling or heating			
Tempering jacket port	G3/8", with quick-open type union, jacket pressure resistance ≤0.4MPa			
Tempering jacket circulation system	prepared by customer, jacket inlet temperature ≤ 8 ° C, cooling water flow > 1.5 L / min			
Discharge materials form	No discharge valve at the bottom of the barrel			
Design environment temperature	-10~+120°C			
Move mode	no			
Mixing Parts				
Working frequency	5-50hz			
Mixing power	0.75kw			
Mixing blade speed	8-76rpm			

Planetary box rotate speed	5-52rpm				
Mixing blade diameter	94mm				
Mixing blade model	Variable section helical twist type, 90° spiral				
Mixing blade material	304 stainless steel				
Mixing blade line speed	0.03-0.37m/s				
Mixing blade number	2pcs				
paddle distance	6±1mm				
Paddle and barrel wall distance	3+1mm				
Paddle and bucket bottom distance	2-3mm				
Dispersing Parts					
Working frequency	5-50hz				
Dispersing power	1.1kw				
Dispersing rotate speed	450-4450rpm				
Dispersing plate diameter	60mm				
Dispersing model	Serrated				
Dispersing plate material	304 stainless steel				
Dispersing line speed	1.3-13m/s				
Dispersing number	1pcs				

Dispersing shaft	1pcs
number	

PRODUCT DISPLAY

