













## XIAMEN TOB NEW ENERGY TECHNOLOGY CO., LTD.

Provide A Full Set Of Solutions For Battery Machines.

SALES tob.amy@tobmachine.com TECH SUPPORT +86-18120715609



## Vacuum Mixing Equipment With Handwheel

This TOB-ZKJB system vacuum mixing equipment is a high efficient equipment with a set of vacuum mixing and dispersion function together, it is suitable for lithium electricity experiment process for anode and cathode paste mixing process, and also other glue, chemical and other industries.

- Item No.:TOB-ZKJB-02
- Order(Mog):1set
- Payment:L/C,T/T,Western Union, Paypal
- Product Origin: China
- Shipping Port:XIAMEN
- Lead Time:7days

## **Product Detail**

1-10L Volume Customized Vacuum Mixing Equipment With Handwheel **Control Without Connecting Air Supply** 

## **SPECIFICATIONS**

- 1 This TOB-ZKJB systemvacuum mixing equipmentis a high efficient equipment with a set of vacuum mixing and dispersion function together, it is suitable for lithium electricity experiment process for anode and cathode paste mixing process, and also other glue, chemical and other industries.
- 2Thevacuum mixeris with handle wheel, which can uplift the cylinder by hand, without connecting with air compressor.
- 3 The vacuum mixing machine is programmable in speed, time, and rotating direction, and water cold stainless steel tank promise high efficient in mixing.
- 4 The TOB-ZKJB system vacuum mixing machineis excellent for preparing LiCoO3, LiFePO4, Phosphors and

ceramic slurry without gas bubble. And the processed material results in the better dispersion and uniformity.

Vacuum mixing equipment TOB-ZKJB-02
AC 220V/110V, 50HZ/60HZ
750W
One Year limited warranty with lifetime support
0-1400 r/min, Through the inverter speed control
2L, 1-10 Liters Customized according request
Arms straight line guide rail hand cover rising, without connecting air compressor
Φ125mm(Diameter)*200mm(Hight)
0-99H can be set
0-80°C Can be set
About 90kg
600*500*300mm, 24"*20"*12"

Advantage	1-10 liter 304 stainless steel container with double layer water cooling jacket.
	Advanced soft sealing type to keep vacuum pressure maintain on -98kpa up to 24 hours.
	Double Step Rotary Vane Vacuum Pump, 254L/m, is included for immediate operation
	Programmable controller to set time, speed, rotation direction.
	With time setting function
	Container is opened or closed by electric Hand (no air pump is required any more)

