Haier Biomedical Intelligent Protection of Life Science





Product advantages

- Manufactured with an internationally branded moisture-proof and flame-retardant glass fiber high efficiency particulate air filters (HEPA), which ensures a filtration efficiency of 99.99% or above for particles of 0.3 or above.
- The air cleanliness conforms to Class 5 of the ISO14644.1 Standard, and is better than Class 100 cleanliness requirements
- With the industry's first pre-cleaning function: namely pre-cleaning the workspace before sample treatment so as to further improve the protection of samples
- · Adopting built-in lighting to prevent the eyes from being exposed to the fluorescent lamp and thus avoids eye strain

One-key operation, convenient and secure:

- With a timed UV lamp turnoff function, it is adjustable between 0 and 99 minutes Interlock function, avoiding the risk of mis-operation
- With the lighting lamp and UV lamp interlock function; the UV lamp can only be lit when the lighting lamp is off. After the fluorescent lamp turned on, the UV lamp will be turn off immediately so that the risk of mis-operation can be reduced to zero



Friendly design

Ergonomic design, making work easier

• The table top is 800mm high from the ground, which is suitable for both standing and sitting operations, relieving any fatigue issues and makes work easy

Delay start of UV sterilization to avoid UV damage

- After the UV lamp switch is pressed down, there will be sound and light signals to remind the operators to leave immediatly, and the UV lamp will light up after a delay of 10 seconds to protect the operator from ultraviolet radiation
- The UV sterilization timed start function ensures less down time of usage and higher efficiencies from the user Split type chassis for easy installation and movement
- •With separated chassis, cabinet body and universal casters with adjustable feet for easy movement and fixation



Product dimensions









HCB-900V







HCB-1300H



HCB-1300V HCB-1600H



Specifications

Model		HCB-900V	HCB-1300V		HCB-1300H			HCB-1600H	
FlowType		Vertical	Vertical		Vertical			Vertical	
Voltage/Frequency		AC 220/50Hz	AC 220/50Hz	AC 115W60Hz	AC 220/50Hz	AC 220/60Hz	AC 115V/60Hz	AC 220/50Hz	AC 220/60Hz
Power(W)		1200	1200		350			350	
Vibration Amplitude (UM)		2	2		2			2	
Exhaust Filter Typical Efficiency		H13 HEPA,99.99%@0.3um	H13 HEPA,99.99%@0.3um		H13 HEPA,99.99%@0.3um			H13 HEPA,99.99%@0.3un	
Average Velocity (M/S)		0.2-0.4	0.2-0.4		0.2-0.4			0.2-0.4	
Fluorescent Lamp Intensity(Lux)		≥300	≥300		≥1000		≥1000		
Net/Gross Weight (approx)	kg	115/145	145/171		145/175		165/214		
	lbs	254/319	320/376		319/385			363.7/471	
Sound Level(dB(A))		58	58		61		61		
Internal Dimensions (W*D*H)	mm	900*530*520	1300*530*520		1310*550*750		1710*550*750		
	in	35.4*20.9*20.5	51.2*20.9*20.5		51.6*21.7*29.6		67.3*21.7*29.6		
External Dimensions (W*D*H)	mm	970*630*1730	1370*630*1730		1380*790*1960		1780*790*1960		
	in	38.2*24.8*68.1	53.9*24.8*68.1		54.4*31.1*77.2		70.1*31.1*77.2		
Packing Dimensions (W*D*H)	mm	1105*745*1280	1505*745*1280		1465*940*1350		1865*940*1370		
	in	43.5*29.3*50.4	59.3*29.3*50.4		57.7*37*53.2		73.4*37.0*53.9		
Cleanliness Classification		ISO 14644.1 Class 5	ISO 14644.1 Class 5		ISO 14644.1 Class 5		ISO 14644.1 Class 5		
Container Load(20'/40'/40'H)		15/33/33	10/25/25		8/16/16			6/12/12	
Certification		CE,TUV,NMPA(CFDA)	CE,TUV,NMPA(CFDA)		CE,TUV		CE,TUV,NMPA(CFDA)		

Qingdao Haier Biomedical Co.,Ltd.

Brand Building, Haier Industrial Park, No. 1 Haier Road, Qingdao, 266101, P.R. China Tel: +86-0532-88935955

Website: www.haiermedical.com











Note:If a slight difference occurs between pictures and actual products, please refer to actual products. Our company reserves the right of final interpretation of this brochure, please contact us for any further information as required.