

CEM

193T1/193H1/193G/193TB1/193HB1/193TN1/193HN1

Plug-PDF Temperature/Humidity/Vibration Dataloggers



193 series Plug-PDF Temperature/Humidity/vibration dataloggers can monitor temperature/humidity/vibration values efficiently and conveniently for long time. 193TB1/193HB1 have bluetooth, the readings can be read on the smartphone by APP software. 193TN1/193HN1 have NB-IOT function, the readings will be up-loaded to cloud server and can be read on the smart phone.

The readings are saved in the logger and simply read out by your PC with USB interface.



EMC
EN: 61326



Model 193H1



Features

| | 193T1 | 193H1 | 193G | 193TB1 | 193HB1 | 193TN1 | 193HN1 |
|--|-------|-------|------|-----------|--------|--------|--------|
| Temperature datalogger | * | | | * | | * | |
| Temperature and humidity datalogger | | * | | | * | | * |
| Temperature ,humidity and vibration datalogger | | | * | | | | |
| Immediately create PDF report in USB flash disk | * | * | * | | | | |
| Freely selectable sample rate 1 min to 24h | * | * | * | | | | |
| LCD Max/ Min display | * | * | * | | | | |
| Download collected data through USB interface | * | * | * | Bluetooth | | NB-IOT | |
| Battery life: up to 1 year (1 minute sample rate) | * | * | * | | | | |
| Alarm LED indication | * | * | * | | | | |
| Analysis software | * | * | * | | | | |

Specifications

| | 193T1/193TB1/193TN1 | 193H1/193HB1/193HN1 | 193G |
|----------------------|---|------------------------------|--------------------------------|
| Temp. range | -30 to 70°C/ -22 to 158°F | -30 to 70°C/ -22 to 158°F | -30 to 70°C/ -22 to 158°F |
| Temp. accuracy | ±1°C/1.8°F | ±1°C/1.8°F | ±1°C/1.8°F |
| Temp. resolution | 0.1°C/0.1°F | 0.1°C/0.1°F | 0.1°C/0.1°F |
| Humidity range | | 0 to 100%RH | 0 to 100%RH |
| Humidity accuracy | | ±3.5%RH | ±3.5%RH |
| Humidity resolution | | 0.1%RH | 0.1%RH |
| vibration range | | | 0 to 16g |
| vibration accuracy | | | ±0.5g |
| vibration resolution | | | 0.1g |
| Memory | 32000 | 32000(16000 /channel) | 30000(T+RH) 1000(vibration) |
| Sample rate | 1min-24 hours | | |
| Battery life | 1year (Sample rate 1minute) | | |
| PDF report | Immediately create PDF report in USB flash disk | | |
| Analysis software | Windows XP/Vista/win7/win8/win10 | | |

Accessories : 3V Lithium battery,software and clamshell.

Size(HxWxD): 95mm x 39mm x 13mm
Weight: 50g

