



DT-355/355W/356/356W/357/358

Professional AC, AC/DC True RMS Autoranging Clamp Meters

The 355 series clamp meters offer all needed features for measurement. It with small bodies and jaws design for perfectly handhold and tight place testing. A large backlit display (on most models) is easy to see and a handy Display Hold keeps measurements on the display.

- Double molded plastic housing
- True RMS measurement for ACV & ACA
- Auto Power Off



Features	DT-355	DT-356	DT-357	DT-355W	DT-356W	DT-358
Current measurement	AC	AC/DC	AC/DC	AC/DC	AC/DC	AC/DC
LCD display counts	6000	6000	40000	6000	6000	50000
AC True RMS	*	*	*	*	*	*
Display with backlight	*	*	*	*	*	*
Data Hold	*	*	*	*	*	*
Max /Min	*	*	*	*	*	*
REL (Zero) Function	*	*	*	*	*	*
Auto Power Off	*	*	*	*	*	*
Low battery indication	*	*	*	*	*	*
Analog Bargraph / 61 seg.	*	*	*	*	*	*
1.57" (40mm) Jaw opening	*	*	*	*	*	*
NCV Detection	*	*	*	*	*	*
USB interface				*	*	
Wireless transmitter				433MHz	915MHz	
Receive Sensitivity				-109dBm		
Communication Distance				≤ 100m		

Size (H x W x D): 230mm x 76mm x 40mm

Weight: 315g

Specifications						
Function	Max Range	Basic Accuracy	DT-355/355W	DT-356/356W	DT-357	DT-358
Voltage DC	600V	$\pm(0.5\%+1d)$	*	*	*	*
Voltage AC	600V	$\pm(1.5\%+2d)$	*	*	*	*
Current DC	1000A	$\pm(2.0\%+5d)$		*	*	*
Current AC	1000A	$\pm(2.5\%+4d)$	*	*	*	*
Resistance	60M Ω	$\pm(3.0\%+5d)$	*	*	*	*
Temperature	760°C/ 1400°F	$\pm(3.0\%+3d)$	*	*	*	*
Capacitance	4000uF	$\pm(2.5\%+5d)$	*	*	*	10mF
Frequency	10MHz	$\pm(1.2\%+2d)$	*	10kHz	10kHz	10kHz
Inrush Current	600A	$\pm(1.5\%+2d)$			*	*
Continuity check	Buzzer sounds at 50 Ω					
Diode test	Test current 0.3mA					

Accessories: Test leads, gift box with carrying case, Temperature probe and 9V battery. USB cable and Software (356W)