

Heating Incubator -natural convection

Microprocessor controller (with timing function)

Summary:

Provided as a necessary equipment for scientific research to colleges as well as biological, agricultural and scientific research departments for storage of mold and biology cultivation.

Features:

- Microprocessor controller (with timing function)
- With inner glass door for easy observation.
- Polished stainless-steel chamber
- Independent temperature-limiting alarm system ensures experiments run safely. (option)
- Printer connector and RS485 connector are options which can connect printer and computer to record the parameters and the variations of temperature. (Option)



Specifications

Model	DHP-9011	DHP-9031	DHP-9051
Electrical Requirement	220V 50Hz		
Temperature Range	RT+5-65℃		
Display Resolution	0.1℃		
Ambient Temperature	+5-35℃		
Power Consumption	85W	125 W	250 W
Chamber Volume	10L	35L	55L
Interior Dimension(W×D×H ,mm)	250×200×200	320×300×320	400×410×360
Exterior Dimension (W×D×H, mm)	460×300×330	530×400×450	640×550×510
Shelves	2PCS		

Oven/Incubator (dual-purpose)

Microprocessor controller (with timing function)

Features:

- Polished stainless-steel chamber, semicircular arcs at corners for easy cleaning, and the space between the shelves in the chamber is adjustable.
- Microprocessor temperature controller ensures a precise and reliable control.
- Forced-air convection
- Double Layer glass door, larger viewing window.
- Independent temperature-limiting Alarm



Options:

- Intelligent programmable temperature controller
- Independent temperature-limiting Alarm system
- RS485 connector

Specifications

Model	PH-010 (A)	PH-030 (A)	PH-050 (A)	PH-070 (A)	PH-140 (A)	PH-240 (A)
Electrical Requirement	220V 50Hz					
Temperature Range	a. as incubator: RT+5-80℃ b.as Oven: 80-220℃					
Display Resolution	0.1℃					
Temperature Accuracy	a. ±0.5℃ b. ±1℃					
Ambient Temperature	+5-35℃					
Power Consumption	650W	850W	1100W	1550W	2050W	2450W
Interior Dimension (W×D×H) mm	250×260×250	340×325×320	420×395×350	450×400×450	550×450×550	600×550×600
Exterior Dimension (W×D×H) mm	530×480×420	620×490×490	720×590×520	740×590×630	840×570×730	800×750×800
Shelves	2(pcs)					
Timing Range	1-5999min					