

DT-968/968W/969/969W

968/969 is a new core algorithm, comprehensive dynamics, night detection, digital signal processing, optical electromechanical integration, and other high-tech. Testing has high precision, stable performance, fast response time, easy to carry, easy to operate. On PM2.5 testing to innovative design and algorithm, greatly reducing the cost of the tester, and reach the international advanced level of similar products.



| Features | | | | | | | | |
|---|-----|------|-----|------|--|--|--|--|
| 2.4' ′ TFT 320 x 240 pixels Color LCD display | 968 | 968W | 969 | 969W | | | | |
| PM2.5/PM10 | * | * | * | * | | | | |
| Air temperature and humidity | * | * | * | * | | | | |
| Analog bar indicator | * | * | * | * | | | | |
| Auto Power Off | * | * | * | * | | | | |
| нсно | | | * | * | | | | |
| Wireless interface | | * | | * | | | | |

| Specifications | | | | | | | | |
|-----------------------------|--|-----|------|-----|------|--|--|--|
| | | 968 | 968W | 969 | 969W | | | |
| Particle Counter Channel | 2.5,10um | * | * | * | * | | | |
| Mass Concentration | PM2.5:0~2000ug/m³ ;PM10:0~2000ug/m³ | * | * | * | * | | | |
| Resolution | 1ug/m³ | * | * | * | * | | | |
| нсно | 0.00~5.00mg/m³ | | | * | * | | | |
| HCHO Accuracy | ±5%F.S | | | * | * | | | |
| Air Temperature Meas | urement | | - | | | | | |
| Air Temp Range | 0 to 50℃/32 to 122℉ | * | * | * | * | | | |
| Basic Accuracy | ±1℃/1.8℉ | * | * | * | * | | | |
| Humidity Range | 0 to 100%RH | * | * | * | * | | | |
| Basic Accuracy | ±5%RH @0 to 20%RH and 80 to 100%RH ±3.5%RH @20 to 80%RH | * | * | * | * | | | |

Accessories: NiMH battery, gift box with carrying case.