

BS-280/280W/288

Video Borescope



High definition 3.5" Color TFT LCD, supporting photo/video, time/date display and multi-languages. Video and images can also be transferred to your PC via the SD Card or USB cable (included). Modern design housing with waterproof (IP67) flexible gooseneck retains configured shape.

- 3.5" Color TFT LCD
- Flexible gooseneck imager head with waterproof and Easily perform visual inspections in hard to reach areas
- Camera and Video function
- Compatible with TV (TV-OUT)
- Allows user to view image on LCD monitor
- High visibility and 10 degree adjustable LED lighting
- Rechargeable battery with USB cable Support SD memory card extension
- Menu with multinational language

Φ17mm 5Mega Pixels Camera Probe



EMC
EN: 61326



Model BS-288

Specifications

	BS-280	BS-280W	BS-288
LCD screen type	3.5" TFT		
LCD Pixels	320x240		
The max number of frames (FPS)	30FPS		30Hz
Picture format from the camera	JPG(640x480)	JPG(640x480/2592x1944)	120 x 90 (InfrarRed resolution)
Camera video format	MP4/AVI (640x480)	MP4/AVI(640x480/720p)	120 x 90 (InfrarRed resolution)
Thermal sensitivity			<60 mk
Temperature range			-20°C to 120°C
Area			3 boxes with max. /min. /average
Color palettes			GRAY/IRON
Auto focus	5 Megapixel		
Gooseneck length	1m(39")		1m(39")
Camera diameter	17mm(0.66")		19.5mm(0.77")
Viewing distance	5cm to 15cm		10cm to ∞
Viewing angle	68°		50°
Zoom and Rotation	3xZoom, 5°/15°/30°/90° rotation	2xZoom, 90° rotation	2xZoom, 90° rotation
Wi-Fi Support system		iOS, Android	iOS, Android
SD card	2GB/Max 32GB		2GB/Max 32GB
Working voltage	Li Battery 3.7V/1800mA		Li Battery 3.7V/1800mA
Language	Support English, French, German, Spanish		Support English, French, German, Spanish



Model BS-280

Wi-Fi Connectivity

Size(HxWxD): 240mm x 160mm x 100mm

Weight: 584g

Accessories:

3.7V Li battery, power adaptor, mirror, hook, magnet, gift box with carrying case.

Accessories:

