



TP-201/TP-201CE



TP-202/TP-202CE



TP-202L/TP-202LCE



TP-203/TP-203CE

TP-202 series Technical Data

MODEL	TP-201/TP-201C E	TP-202/TP-202C E	TP-202L/TP-202 LCE	TP-203/TP-203C E
Electrical Requirements	110V/220V/230V/240V (50/60Hz) 1PH			
Strapping Capacity	2.5 seconds / Cycle (60Hz)			
Strap Requirement	strap width: 6 ~ 9 mm with strap thickness: 0.5 ~ 0.65 mm strap width: 12 ~ 15.5 mm with strap thickness: 0.5 ~ 0.75 mm			
Tension Range	15 to 45kg			9 to 30kg
Dimension (W) × (D) × (H)	902×586×775mm	902×586×760mm	1476×586×372mm	632×422×805mm
Table Height	775 mm	760 mm	372 mm	805 mm
Machine Net Weight	100 kg	85 kg	80 kg	80 kg
Maximum Package Weight	100 kg			70 kg
Minimum Package Size	80W × 20H mm			
Strap Core Inner Diameter	200 mm / 230mm / 280 mm (interchangeable)			

Power Consumption	0.25 kW
Temperature of working environment	5 ~ 40°C