

**THE ASIA'S
TECHNOLOGY LEADER**

A SINGLE-SOURCE SUPPLIER OF STRAPPING MACHINE



**THE ASIA'S
TECHNOLOGY
LEADER**

A SINGLE-SOURCE SUPPLIER OF STRAPPING MACHINE



[Home](#) > [PRODUCTS](#) > [Corrugated Strapping Machines](#) > [TP-702CCQ Corrugated 3-Side Bundle Squaring and Strapping System](#)

PRODUCTS

- [Strapping Tools](#)
- [Semi-Auto Strapping Machines](#)
- [Automatic Strapping Machines](#)
- [Fully Automatic Strapping Machines](#)
- [Corrugated Strapping Machines](#)
- [Print Media Strapping Machines](#)
- [Side-Seal Strapping Machines](#)



TP-702CCQ is built based on TP-702C high speed corrugated strapper combined with the 3-side squaring station CC-BSS. It carries all the innovative features of TP-702C. TP-702CCQ offers high strapping productivity with the most cost-effective bundle squaring solution for corrugated industry.



[INQUIRY](#)

Features

- Compact & robust strapping head
- 3-side squaring bundle control
- Siemens PLC
- Free access to strap guides (*patents registered*)
- Hinged roller table
- Auto strap ejector
- Patented jammed-strap ejection device
- Full-width pneumatic press
- Multiple strap function
- Variable conveyor speed
- Adjustable pressure on press and squaring

Options

- Siemens HMI (touch panel)
- Light tower with low strap sensor
- Foot pedal switch
- Strapping cycle counter
- Squaring plate extension for bundle length up to 1520 mm
- Adjustable backstop

Technical Data

Arch Size	TP-702CCQ-L 1650 mm(W) x 450 mm(H) TP-702CCQ-M 1250 mm(W) x 450 mm(H)
Strap Width	5 mm, 6 mm, or 9 mm
Tension Range	1 - 32 kg
Capacity	Up to 26 bundles/minute (single strap) Up to 20 bundles/minute (double straps) (Model: TP-702CCQ-L)
Minimum Bundle Size	200 mm(W) x 20 mm(H) x 300 mm(L)
Bundle Weight	max 40 kg
Conveyor Speed	15 - 60 M/minute
Electrical Requirements	220V, 380V, 400V, 415V 50/60Hz 3PH



(0)

[CONTACT](#)

[DISTRIBUTOR SITE](#)

[EN/中文/JP](#) ▾



Search

[PRODUCTS](#)

[INDUSTRY SOLUTIONS](#)

[ABOUT US](#)

[NEWS](#)

[FAQ](#)

FAX +886 2 2555 2516