

# TB100 Portable Turbidity Meter



## Features

- High-performance portable turbidity meter meets the design criteria in ISO 7027
- 2 to 5 points calibration using the Formazin Standards
- Selectable 4 turbidity units, including the NTU, FNU, EBC and ASBC
- Single measurement mode automatically senses and locks a stable reading
- Continuous measurement mode can be used for indexing or matching the sample vials
- Auto-Power Off effectively conserves battery life
- Setup menu allows setting the number of calibration points, resolution, date and time, etc.
- Reset function automatically resumes all settings back to the factory defaults
- Expanded memory stores or recalls up to 100 data sets
- USB communication interface for data transfer or connecting a power adapter to meter

## Ordering Information

TB100: Meter, turbidity standards (0.02, 200, 500, 1000 NTU), sample vials, lint-free cloth and carrying case



## Specifications

Model		TB100
Turbidity	Principle	ISO 7027 nephelometric method (90°)
	Range	0~1100 NTU, 0~275 EBC, 0~9999 ASBC
	Resolution	0.01 (0~99 NTU), 0.1 (100~999 NTU), 1 (1000~1100 NTU)
	Accuracy	±2% of reading (0~500 NTU), ±3% of reading (501~1100 NTU)
	Calibration Points	2 to 5 points
	Calibration Standards	0.02, 10, 200, 500, 1000 NTU
Other Specifications	Light Source	Infrared-emitting diode (850nm wavelength)
	Detector	Silicon photodiode
	Stray Light	<0.02 NTU
	Sample Vial	60(H)×25(Dia)mm
	Sample Volume	30mL
	Memory	100 data sets
	Communication Interface	USB
	Operating Temperature	0~50°C
	Display	Custom LCD (60×40 mm)
	Power Requirements	3×1.5V AA batteries or DC5V power adapter
Dimensions	180(L)×85(W)×70(H)mm	
Weight	300g	