

# YP1002 YP Series Electronic Balance

Weighing Range: 0-100g, Readable Precision: 10mg, Scale Size:  $\Phi$ 125mm

YP series electronic balance, Modern conception is reflected in the facile and originative appearance design. New design makes weighing reaction and position-fixed more quick, the unique metallic base and mechanical structure ensure the stability of balances and improves the interference immunity of balances. We can make product according with the clients' request. the instrument is portable and can be operated outdoors.



Feature:

- Being equipped with both AC and DC power source, having gradienter back-lighted
- LED , react quickly, more stable

Function :

- System operating: counting, percentage, automatic calibrating, calibrating point selecting,calibrating weigh(optional).
- Multip functions guaranteee easy and reliable operation,including auto-counting,unit conversion(metric carat,gole ounce,etc.),stablility,full-scale faring,zero-memory,etc
- Bilit-in RS232C output interface guarantees direct connection to external equipemnt such ascomputer and printer

Spec:

Model	Weight Range	Readable Precision	Outer Dimension	Packag Size	Electricity	Pan Dimension	N. W
YP1002	0-100g	10mg	250×180×60 mm	325×245×152 mm	AC/DC	Φ125mm	1kg
YP2002	0-200g	10mg	250×180×60 mm	325×245×152 mm	AC/DC	Φ125mm	1kg
YP3002	0-300g	10mg	250×180×60 mm	325×245×152 mm	AC/DC	Φ125mm	1kg
YP4002	0-400g	10mg	250×180×60 mm	325×245×152 mm	AC/DC	Φ125mm	1kg
YP5002	0-500g	10mg	250×180×60 mm	325×245×152 mm	AC/DC	Φ125mm	1kg
YP6002	0-600g	10mg	250×180×60 mm	325×245×152 mm	AC/DC	Φ125mm	1kg
YP10002	0-1000g	10mg	250×180×60 mm	325×245×152 mm	AC/DC	130×130× mm	1kg
YP20002	0-2000g	10mg	250×180×60 mm	325×245×152 mm	AC/DC	130×130× mm	1kg
YP30002	0-3000g	10mg	250×180×60 mm	325×245×152 mm	AC/DC	160×160× mm	1kg
YP2001	0-200g	100mg	250×180×60 mm	325×245×152 mm	AC/DC	Φ125mm	1kg
YP4001	0-400g	100mg	250×180×60 mm	325×245×152 mm	AC/DC	Φ125mm	1kg
YP5001	0-500g	100mg	250×180×60 mm	325×245×152 mm	AC/DC	Φ125mm	1kg
YP6001	0-600g	100mg	250×180×60 mm	325×245×152 mm	AC/DC	Φ125mm	1kg
YP8001	0-800g	100mg	250×180×60 mm	325×245×152 mm	AC/DC	Φ125mm	1kg
YP10001	0-1000g	100mg	250×180×60 mm	325×245×152 mm	AC/DC	130×130mm	1kg
YP160	0-	100mg	250×180×60	325×245×152	AC/DC	130×130m	1kg

01	1600g		mm	mm		m	
YP200 01	0- 2000g	100mg	250×180×60 mm	325×245×152 mm	AC/DC	130×130m m	1kg
YP300 01	0- 3000g	100mg	250×180×60 mm	325×245×152 mm	AC/DC	160×160m m	1.3k g
YP400 01	0- 4000g	100mg	250×180×60 mm	325×245×152 mm	AC/DC	160×160m m	1.3k g
YP500 01	0- 5000g	100mg	250×180×60 mm	325×245×152 mm	AC/DC	160×160m m	1.3k g
YP600 01	0- 6000g	100mg	250×180×60 mm	325×245×152 mm	AC/DC	160×160m m	1.3k g
YP800 01	0- 8000g	100mg	250×180×60 mm	325×245×152 mm	AC/DC	160×160m m	1.3k g
YP100 0	0- 1000g	1g	250×180×60 mm	325×245×152 mm	AC/DC	130×130m m	1kg
YP200 0	0- 2000g	1g	250×180×60 mm	325×245×152 mm	AC/DC	130×130m m	1kg
YP300 0	0- 3000g	1g	250×180×60 mm	325×245×152 mm	AC/DC	160×160m m	1kg
YP600 0	0- 6000g	1g	250×180×60 mm	325×245×152 mm	AC/DC	160×160m m	1kg